

Today: Trees


Computer Programming 143 – Lecture 29

Dynamic Data Structures III

Faculty of Engineering



Informal tree introduction



12.7 Trees II

```
struct treeNode {  
    struct treeNode *leftPtr;  
    int data;  
    struct treeNode *rightPtr;  
};  
typedef struct treeNode TreeNode;  
typedef struct treeNode *TreeNodePtr;
```


TreeNode




Use of trees

- Efficient search and sorting algorithms
- Store and evaluation of mathematical expressions


Tree concepts



12.7 Sorted Binary Trees II



12.7 Insertion in Sorted Binary Trees




12.7 Traversal of Sorted Binary Trees I

Order of traversal of trees

- For some applications, all the nodes of the tree need to be visited
- The order in which the nodes are visited vary and may include:
 - ✈ • Inorder: at each node,
 - 1 Traverse the node's left subtree
 - 2 Process the node value
 - 3 Traverse the node's right subtree
 - Preorder: at each node,
 - 1 Process the node value
 - 2 Traverse the node's left subtree
 - 3 Traverse the node's right subtree
 - Postorder: at each node,
 - 1 Traverse the node's left subtree
 - 2 Traverse the node's right subtree
 - 3 Process the node value
- Easily implemented using recursive functions

12.7 Inorder Traversal of Trees

```
void inOrder( TreeNodePtr treePtr )
{
    if ( treePtr != NULL ) {
        inOrder( treePtr->leftPtr );
        printf( "%3d", treePtr->data );
        inOrder( treePtr->rightPtr );
    }
}
```




Output

1 2 4 5

12.7 Inorder Traversal of Trees

```
void inOrder( TreeNodePtr treePtr )  
{  
    if ( treePtr != NULL ) {  
        inOrder( treePtr->leftPtr );  
        printf( "%3d", treePtr->data );  
        inOrder( treePtr->rightPtr );  
    }  
}
```



Output

1 2 4 5 6 7 9

1 2 4 5 6 7 9

Inorder traversal of trees

```

void inOrder(TreeNodePtr treePtr)
{
    if (treePtr != NULL)
    {
        inOrder(treePtr->leftPtr);
        printf("%3d", treePtr->data);
        inOrder(treePtr->rightPtr);
    }
}

```

```

main()
{
    TreeNodePtr root = &a;
    inOrder(&a);
    ...
}

```

```

void inOrder((a))
{
    inOrder((b));
}

```

```

void inOrder((b))
{
    inOrder((c));
    printf(data);
    inOrder((d));
}

```

```

void inOrder(NULL)
{
    // nothing
}

```

```


void inOrder((c))
{
    inOrder(NULL);
    printf(data);
    inOrder(NULL);
}

```

```


void inOrder(NULL)
{
    //nothing
}

```



12.7 Preorder Traversal of Trees

```
void preOrder( TreeNodePtr treePtr )
{
    if ( treePtr != NULL ) {
        printf( "%3d", treePtr->data );
        preOrder( treePtr->leftPtr );
        preOrder( treePtr->rightPtr );
    }
}
```




Output

5 2 1 4 7 6 9

12.7 Postorder Traversal of Trees

```
void postOrder( TreeNodePtr treePtr )
{
    if ( treePtr != NULL ) {
        postOrder( treePtr->leftPtr );
        postOrder( treePtr->rightPtr );
        printf( "%3d", treePtr->data );
    }
}
```




Output

1 4 2 6 9 7 5

✓✓✓

Examples of trees








Figure 4.4: An example of a multi-accent decision-tree, taking into account the accent of the clustered triphone HMM states as well as the phonetic character of the left and right contexts.